

Speedflow

B

Unvented Water Heater

5, 10 and 15 litre

Glass Lined or Stainless Steel Tank



p.34

Usage

Ideal for use in cloakrooms and kitchens in offices, shops, student accommodation and domestic premises which have been extended and there is no central hot water system near by. One unit located under the kitchen sink is often used to supply hot water for light dishwashing in the kitchen sink and handwashing in the cloakroom basin.

Selection Guide (approximate depending on usage).



1 basin: **SF05K**, 1 – 2 basins: **SF10K**, 2 – 3 basins: **SF15K**

Features and Benefits

- Supplies hot water for up to 3 basins
- Can be used with regular taps including mixers
- Mains pressure flow rates
- 2.0 kW element as standard
- 1.2 kW element available for 10 and 15 litre models for restricted load applications
- Neon element on indicator
- Glass lined steel tank as standard
- **Stainless steel tank available for the 10 and 15 litre models. Add suffix SS to the product code.**
- External temperature control with frost protection setting
- Accessories may be needed to comply with the Water Regulations. Pressure reducing valve required for pressures above 4.2 bar and expansion vessel and check valve required if cold water draw off nearby. Kits available separately (see Speedflow Accessories).
- Optional thermostatic mixing valve available (see page 40)
- Not suitable for hair wash basins in hairdressing salons

Product Code	Capacity (litres)	Power (kW)	Heat Up Time (mins)*	Standing Loss (kWh/day)
SF05K	5	2.0	12	0.51
SF10K, SF10KSS SF10K12, SF10K12SS	10	2.0 1.2	23 38	0.63
SF15K, SF15KSS SF15K12, SF15K12SS	15	2.0 1.2	35 57	0.71

*Approximate heat up time from 10°C to 75°C



Outer Casing
Easy clean, high impact plastic

Heating Element
Stainless steel flange type

Thermostat
Bulb type adj. to 75°C
E setting approx. 50°C

Water Tank
Glass lined steel as standard.
Stainless steel tank
optional upgrade.

Anode
Replaceable grey magnesium
(inspect annually)

Insulation
High density polyurethane foam

Safety
Overheat temperature
protection (manual reset).
Supplied pressure relief valve
must be fitted in every case
(set at 6 bar).
Frost protection if power on.
Optional thermostatic mixing valve
to maintain hot water supplied to
user at constant, safe temperature.

IP Rating
IPX4

Installation
Site above or below the sink, but
inlet and outlet must be at the top.
Floor standing or wall mounted.

Plumbing
Must be installed by a suitably
qualified person.

It is recommended that flexible
hoses are used for connection to
facilitate future maintenance.
Access to the thermal cut-out and
element is located at base of unit.

Minimum water pressure 0.5 bar.
Maximum water pressure 4.2 bar.

Water Connection
Inlet/ Outlet 2 x 1/2" BSP male
(100mm apart centre to centre).
Fittings required (not supplied):
2 x 15mm compression to 1/2"
BSP female adapter.

Electrical Connection
Installation must comply with
current IEE regulations.

The product should be connected
to the fixed wiring of the property
via a double pole fused spur
with a minimum break capacity
of 13 amps.
Cable pre-wired (1.5m).

Approvals
CE, WRAS

Standard Warranty
Glass Lined Tank
1 year parts or replacement
warranty.
Stainless Steel Tank
3 year tank warranty.

Product Code	Height (mm)	Width (mm)	Depth (mm)	Weight (kg)	
				Empty	Full
SF05K	320	280	245	5.5	10.5
SF10K, SF10KSS SF10K12, SF10K12SS	410	310	280	6.8	16.8
SF15K, SF15KSS SF15K12, SF15K12SS	530	310	280	8.3	23.3